

# Technical Data

## Low pressure version - 2964 Series

### Material




Sleeve: Aluminium alloy

(BS1473/4/5 - 6061/AA6061 EN 573-3 AlMg1SiCu Werkstoff 3.3211)

Stem: Carbon steel, hardened and tempered,

Zinc plated, clear trivalent passivated with top seal

(BS 3111 type 10 DIN 1654 35B2)



Taper hole entry only required  
for automated assembly.

| $\varnothing$ | O    | $\varnothing$ B | $\varnothing$ A | L    | $\varnothing$ C | $\varnothing$ H |      |      | P <sup>1)</sup> | M <sup>1)</sup> |       | Part No     |
|---------------|------|-----------------|-----------------|------|-----------------|-----------------|------|------|-----------------|-----------------|-------|-------------|
|               | max. | ref.            | max.            | max. | ref.            | min.            | max. | rec. | req.            | min.            | max.  |             |
| 8.0           | 50.8 | 6.0             | 7.9             | 7.8  | 3.55            | 8.0             | 8.15 | 8.0  | 9.90            | 7.50            | 9.50  | 02910-10790 |
| 9.0           | 51.8 | 6.1             | 8.8             | 8.5  | 3.58            | 9.0             | 9.4  | 9.0  | 11.71           | 7.19            | 10.57 | 02964-00911 |
| 10.0          | 52.6 | 7.0             | 9.8             | 9.5  | 3.90            | 10.0            | 10.4 | 10.2 | 13.05           | 8.81            | 11.46 | 02964-01012 |
| 11.0          | 53.4 | 7.8             | 10.8            | 9.8  | 4.40            | 11.0            | 11.4 | 11.2 | 13.66           | 9.41            | 12.11 | 02964-01113 |
| 12.0          | 53.4 | 7.8             | 11.8            | 9.5  | 4.40            | 12.0            | 12.4 | 12.2 | 13.43           | 9.45            | 11.96 | 02964-01215 |
| 13.0          | 62.0 | 8.6             | 12.8            | 10.3 | 4.80            | 13.0            | 13.4 | 13.2 | 14.74           | 10.04           | 12.51 | 02964-01315 |
| 14.0          | 62.8 | 9.4             | 13.8            | 11.0 | 5.30            | 14.0            | 14.4 | 14.2 | 15.65           | 11.70           | 13.87 | 02964-01415 |
| 16.0          | 64.8 | 11.0            | 15.8            | 12.6 | 6.00            | 16.0            | 16.4 | 16.2 | 18.04           | 13.88           | 16.00 | 02964-01620 |

all dimensions in mm

1) Values for use with a flat nose tip (except for 4.0 & 5.0 mm where only stepped nose tips are available):

- Add „S“ = 1 mm / 2 mm / 8 mm to „P“ and „M“ values when a 1 mm / 2 mm / 8 mm extended nose tip is used

# Avseal® II

The Avseal II range of blind sealing plugs can be installed with the current selection of structural hand tools and automated placing equipment.

The tapered end of the plug's stem ensures it is easy to feed into the tooling equipment, while the taper on the sleeve allows ease of entry into an application.

## Hand Tools



Range of Genesis® nG models



73200 model



734 AV™ model



## Placing Matrix

| Diameter | Recommended Hand Tools |            |            |       |        |
|----------|------------------------|------------|------------|-------|--------|
|          | nG2/nG2-S              | nG3        | nG4        | 73200 | 734 AV |
| 4 mm     | 2961                   |            |            |       |        |
| 5 mm     | 2961                   |            |            |       |        |
| 6 mm     | 2961                   | 2961       |            |       |        |
| 7 mm     | 2961                   | 2961       | 2961       |       |        |
| 8 mm     |                        | 2961, 2964 | 2961, 2964 |       |        |
| 9 mm     |                        | 2964       | 2961, 2964 |       |        |
| 10 mm    |                        |            | 2961, 2964 |       |        |
| 11 mm    |                        |            | 2964       | 2961  |        |
| 12 mm    |                        |            | 2964       | 2961  |        |
| 13 mm    |                        |            |            | 2964  |        |
| 14 mm    |                        |            |            |       | 2964   |
| 16 mm    |                        |            |            |       | 2964   |

2961 series (High pressure version)    2964 series (Low pressure version)  
Other tools available, please ask your STANLEY Engineered Fastening contact.