



Pneumatic pump 1:1-NEF

SRL 860-200/220-l-container

Item number: 19 135
EAN: 4103810191350
Discount group: D

Technical data

Length of suction tube (mm): 860
Pressure ratio: 1:1
Max. diameter (mm): 130
Max. air pressure (bar): 10
Min. air pressure (bar): 2
Recommended air pressure (bar): 8
Cylinder capacity engine cm³: 220
Cylinder capacity pump cm³: 220
Quantity of strokes at 8 bar at a free-flow (min.): 240
Pump capacity at 8 bar at a free-flow (l/min): 66
Pump pressure at 8 bar air pressure (bar): 8
Air consumption at 8 bar air pressure (l/min): 450
Length of discharge pipe work: Depends on size of installation.
Max. suction height: 6 m, suction tube G 1"
Compressed air connection: G 1/4" female
Oil connection - suction side: G 1" female
Oil connection - delivery side: G 3/4" male
Connection container: G 2" male, drum adapter
Noise level idle running acc. to ISO 9614-2 at a distance of 2 m (db A): 78
Noise level under load acc. to ISO 9614-2 at a distance of 2 m (db A): 77
Viscosity of discharged liquid: oil up to ISO VG 15 SAE 5
Classical liquids to be discharged: diesel and oil
Time duration for 1 complete container draining: 200 l diesel in 3 minutes
Lacquering: blue, Pantone 294 C
Length of engine (mm): 375
Weight (kg): 6,92

Specification

- pneumatic oil- and diesel pump 1:1.
- Can not be calibrated for public sales (NEF)
- For 200/220 l container
- suction tube G 1" male
- To discharge low viscosity self-lubricating liquids, such as diesel, fuel oil and engine oil
- Due to its high delivery rate, it can be used as a filling pump

Special notes

- Operate pneumatic pump with maintenance unit (20 218 950)

Packaging

Dimensions LxWxH (mm): 1310 x 190 x 195
Weight (kg): 7,74
Packing unit: 1.0